

EARTHMAX SR 48 - Specifiche tecniche



Description

EARTHMAX SR 48 è uno pneumatico All Steel specificamente sviluppato per dumper rigidi. Questo pneumatico assicura maggiore trazione e straordinaria resistenza all'usura anche nelle operazioni più ardue in ambienti rocciosi. È ideale per il trasporto di carichi pesanti. La spalla di forma quadrata protegge il fianco da tagli e danni. EARTHMAX SR 48 mostra una robusta carcassa All Steel che offre eccezionale protezione contro urti e perforazioni di sassi ottimizzando la produttività.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper rigido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	510
Overall Width (mm)	738
Overall Diameter (mm)	2688
Static Loaded Radius (mm)	1225
Rolling Circumference (mm)	8165
Rim Rec	19.50/4.0
Rim Alt	--
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Printed on 25/04/2024 21:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..