

## EARTHMAX SR 49 - Specifiche tecniche



### Description

EARTHMAX SR 49 (L-4) è uno pneumatico radiale All Steel progettato per loader e dozer, dumper di basso profilo (LPDT) e pale LHD. EARTHMAX SR 49 assicura ottime prestazioni nelle operazioni esigenti in miniera dove trazione e stabilità eccellenti rappresentano un requisito essenziale. Lo pneumatico ha un disegno direzionale ed è realizzato con una miscela particolarmente resistente ai tagli che garantisce eccellente durabilità.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dozer • Pala LHD • Pala caricatrice • Dumper di basso profilo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	35/65 R 33
LI/SS	229 A2

## Dimensions US Standard

Usa code	94057115
Overall Width (inch)	35.4
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	35
Rolling Circumference (inch)	241.1
Rim Rec	28.00/3.5
Rim Alt	--
Star Rating	***
TRA Code	L4

## Load capacity (lbs)

mph / psi	98	102	105	109	112	116
5	64000	66000	68000	69500	70500	71500

Printed on 19/04/2024 18:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..