

EARTHMAX SR 49 - Specifiche tecniche



Description

EARTHMAX SR 49 (L-4) è uno pneumatico radiale All Steel progettato per loader e dozer, dumper di basso profilo (LPDT) e pale LHD. EARTHMAX SR 49 assicura ottime prestazioni nelle operazioni esigenti in miniera dove trazione e stabilità eccellenti rappresentano un requisito essenziale. Lo pneumatico ha un disegno direzionale ed è realizzato con una miscela particolarmente resistente ai tagli che garantisce eccellente durabilità.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Pala LHD • Pala caricatrice • Dumper di basso profilo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	45/65 R 45
LI/SS	245 A2

Dimensions US Standard

Usa code	94067572
Overall Width (inch)	44.5
Overall Diameter (inch)	107.5
Static Loaded Radius (inch)	46.9
Rolling Circumference (inch)	319.4
Rim Rec	36.00/4.5
Star Rating	**
TRA Code	L4
Tread Depth	91

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	96500	99000	102000	104500	110000	113500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/03/2025 13:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..