

## EARTHMAX SR 49 - Scheda tecnica



### Description

EARTHMAX SR 49 (L-4) è uno pneumatico radiale All Steel progettato per loader e dozer, dumper di basso profilo (LPDT) e pale LHD. EARTHMAX SR 49 assicura ottime prestazioni nelle operazioni esigenti in miniera dove trazione e stabilità eccellenti rappresentano un requisito essenziale. Lo pneumatico ha un disegno direzionale ed è realizzato con una miscela particolarmente resistente ai tagli che garantisce eccellente durabilità.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dozer • Pala LHD • Pala caricatrice • Dumper di basso profilo

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
35/65 R 33	CUT RESISTANT COMPOUND	L4	***	229 A2	28.00/3.5	--	899	2061	890	6125	TL	59
35/65 R 33	CUT RESISTANT COMPOUND	E4/L4	****/***		28.00/3.5	--	899	2061	890	6125	TL	59
35/65 R 33	CUT RESISTANT COMPOUND	L4	**	224 A2	28.00/3.5	--	899	2061	890	6125	TL	59
35/65 R 33	CUT RESISTANT COMPOUND	SH4	****		28.00/3.5	--	899	2061	890	6125	TL	59
45/65 R 45	CUT RESISTANT COMPOUND	L4	**	245 A2	36.00/4.5		1130	2730	1190	8113	TL	72

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/03/2025 13:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..