

EARTHMAX SR 50 - Specifiche tecniche



Description

EARTHMAX SR 50 (L-5) è uno pneumatico radiale **All Steel** particolarmente progettato per loader. La carcassa durevole e i cordoli di protezione sono ideali per le operazioni più esigenti. EARTHMAX SR 50 è realizzato in una miscela speciale resistente ai tagli che riduce l'usura assicurando una vita più lunga allo pneumatico. Gli operatori apprezzeranno anche l'eccellente trazione abbinata a stabilità e guida confortevole.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	209 A2

Dimensions US Standard

Usa code	94037070
Overall Width (inch)	27.2
Overall Diameter (inch)	69.8
Static Loaded Radius (inch)	31.7
Rolling Circumference (inch)	210
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L5

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	34200	35300	36400	37500	39700	40800

Printed on 26/02/2024 01:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..