

EARTHMAX SR 50 - Specifiche tecniche



Description

EARTHMAX SR 50 (L-5) è uno pneumatico radiale **All Steel** particolarmente progettato per loader. La carcassa durevole e i cordoli di protezione sono ideali per le operazioni più esigenti. EARTHMAX SR 50 è realizzato in una miscela speciale resistente ai tagli che riduce l'usura assicurando una vita più lunga allo pneumatico. Gli operatori apprezzeranno anche l'eccellente trazione abbinata a stabilità e guida confortevole.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	208 A2

Dimensions International Standard

Overall Width (mm)	775
Overall Diameter (mm)	1901
Static Loaded Radius (mm)	862
Rolling Circumference (mm)	5722
Rim Rec	25.00/3.5
Star Rating	*
TRA Code	L5

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00
10	15500	16000	17000	17500	18000

Printed on 22/02/2024 18:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..