

EARTHMAX SR 51 - Specifiche tecniche



Description

EARTHMAX SR 51 (L-5) è uno pneumatico radiale **All Steel** particolarmente sviluppato per loader e dozer. EARTHMAX SR 51 è ideale per operazioni dure che richiedono addizionale resistenza al taglio nonché protezione dei fianchi ed eccezionale trazione.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	201 A2

Dimensions US Standard

Usa code	94069828
Overall Width (inch)	24.1
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	29.3
Rolling Circumference (inch)	192.2
Rim Rec	19.50/2.5
Star Rating	**
TRA Code	L5

Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	27600	28300	29100	30000	30900	32000

Printed on 17/04/2024 03:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..