

EARTHMAX SR 51 - Scheda tecnica



Description

EARTHMAX SR 51 (L-5) è uno pneumatico radiale **All Steel** particolarmente sviluppato per loader e dozer. EARTHMAX SR 51 è ideale per operazioni dure che richiedono addizionale resistenza al taglio nonché protezione dei fianchi ed eccezionale trazione.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Pala caricatrice

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
17.5 R 25	CUT RESISTANT COMPOUND	L5	*	176 A2	14.00/1.5		437	1398	630	4110	TL
20.5 R 25	CUT RESISTANT COMPOUND	L5	*	186 A2	17.00/2.0		539	1545	703	4650	TL
23.5 R 25	CUT RESISTANT COMPOUND	L5	*	195 A2	19.50/2.5		612	1660	743	4882	TL
23.5 R 25	CUT RESISTANT COMPOUND	L5	**	201 A2	19.50/2.5		612	1660	743	4882	TL
29.5 R 29	CUT RESISTANT COMPOUND	L5	*	211 A2	25.00/3.5	24.00/3.5, 26.00/3.5	777	1990	842	5872	TL
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	L5	**	221 A2	27.00/3.5	27.00/3.0; 28.00/3.5	878	1872	814	5616	TL
35/65 R 33	CUT RESISTANT COMPOUND	L5	**	224 A2	28.00/3.5		905	2061	872	6082	TL
35/65 R 33	CUT RESISTANT COMPOUND	L5	***	229 A2	28.00/3.5		905	2061	872	6082	TL

Printed on 17/04/2024 04:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..