

EARTHMAX SR 51 - Scheda tecnica



Description

EARTHMAX SR 51 (L-5) è uno pneumatico radiale *All Steel* particolarmente sviluppato per loader e dozer. EARTHMAX SR 51 è ideale per operazioni dure che richiedono addizionale resistenza al taglio nonché protezione dei fianchi ed eccezionale trazione.

UM

US Standard

Construction

RADIAL

Machinery

OTR: Dozer, Pala caricatrice

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
17.5 R 25	CUT RESISTANT COMPOUND	94046249	L5	*	176 A2	14.00/1.5	14.00LR/1.5;13.00LR/1.41	17.2	55	24.8	161.8	TL
20.5 R 25	CUT RESISTANT COMPOUND	94045822	L5	*	186 A2	17.00/2.0	17.00AL/1.7	21.2	60.8	27.7	183.1	TL
23.5 R 25	CUT RESISTANT COMPOUND	94046256	L5	*	195 A2	19.50/2.5	19.50/2.5 IF	24.1	65.4	29.3	192.2	TL
23.5 R 25	CUT RESISTANT COMPOUND	94069828	L5	**	201 A2	19.50/2.5		24.1	65.4	29.3	192.2	TL
29.5 R 29	CUT RESISTANT COMPOUND	94051113	L5	*	211 A2	25.00/3.5	24.00/3.5, 26.00/3.5	30.6	78.3	33.1	231.2	TL
875/65 R 29 (35/65 R 29)	CUT RESISTANT COMPOUND	94067145	L5	**	221 A2	27.00/3.5	27.00/3.0; 28.00/3.5	34.6	73.7	32	221.1	TL
35/65 R 33	CUT RESISTANT COMPOUND	94066230	L5	**	224 A2	28.00/3.5		35.6	81.1	34.3	239.4	TL

Printed on 21/05/2022 17:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..