EARTHMAX SR 55 - Specifiche tecniche

Description

EARTHMAX SR 55 è uno pneumatico radiale All Steel specialmente progettato per loader, dozer e pale LHD che operano nelle condizioni più severe come nelle cave e miniere, nonché nei cantieri di demolizione. Grazie al disegno del battistrada extra profondo e liscio EARTHMAX SR 55 è in grado di raggiungere elevati picchi di produttività con minori tempi di fermo macchina, assicurando ottima durabilità. Gli operatori delle macchine apprezzeranno anche stabilità e trazione straordinarie.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Dozer • Pala LHD • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 29
LI/SS	218 A2

Dimensions International Standard

Overall Width (mm)	775
Overall Diameter (mm)	2009
Static Loaded Radius (mm)	911
Rolling Circumference (mm)	6047
Rim Rec	25.00/3.5
Rim Alt	24.00/3.5, 26.00/3.5
Star Rating	**
TRA Code	L5S

Load capacity (Kg)

km/h / bar	5.25	5.50	5.75	6.00	6.25	6.50
10	20000	20600	21200	22400	23000	23600

Printed on 26/04/2024 17:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..