

EARTHMAX SR 57 - Specifiche tecniche



Description

EARTHMAX SR 57 è uno pneumatico radiale All Steel particolarmente progettato per loader, dozer e veicoli universali impiegati nelle miniere sotterranee. Lo pneumatico assicura trazione superiore, stabilità e comfort su superfici ruvide e rocciose. Il battistrada extra profondo L-5, insieme alla miscela con speciale formula UMS (underground mine service), garantisce una maggiore resistenza all'usura oltre a straordinaria resistenza contro tagli di roccia e forature.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dozer • Pala LHD • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TT
Tyre Size	12.00 R 20

Dimensions International Standard

Overall Width (mm)	318
Overall Diameter (mm)	1180
Rim Rec	8.50
Star Rating	*
TRA Code	L5

Load capacity (Kg)

km/h / bar	7.00
6	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 08/12/2024 16:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..