

EARTHMAX SR LOADER - Specifiche tecniche



Description

EARTHMAX SR LOADER è uno pneumatico OTR particolarmente progettato per le operazioni di carico e spianamento, nonché per applicazioni di trasporto con dumper articolati. La sua carcassa All Steel rinforzata con cinture in acciaio multistrato e l'esclusiva mescola del battistrada offrono eccezionale resistenza a strappi e forature che si traducono in una vita prolungata dello pneumatico. EARTHMAX SR LOADER è dotato di un esclusivo disegno del battistrada che assicura ottime proprietà autopulenti e trazione eccellente su svariati tipi di terreno.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/195 A2

Dimensions US Standard

Usa code	94060283
TMPH	137
Overall Width (inch)	24.1
Overall Diameter (inch)	63.2
Static Loaded Radius (inch)	27.8
Rolling Circumference (inch)	187.8
Rim Rec	19.50/2.5
Rim Alt	--
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	16500	17100	18200	18700	19800	20400
5	22700	23400	24700	25400	26800	-

Printed on 24/04/2024 11:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..