

EARTHMAX SR LOADER - Specifiche tecniche



Description

EARTHMAX SR LOADER è un pneumatico OTR particolarmente progettato per le operazioni di carico e spianamento, nonché per applicazioni di trasporto con dumper articolati. La sua carcassa All Steel rinforzata con cinture in acciaio multistrato e l'esclusiva mescola del battistrada offrono eccezionale resistenza a strappi e forature che si traducono in una vita prolungata dello pneumatico. EARTHMAX SR LOADER è dotato di un esclusivo disegno del battistrada che assicura ottime proprietà autopulenti e trazione eccellente su svariati tipi di terreno.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

Dimensions US Standard

Usa code	94065608
TMPH	185
Overall Width (inch)	30.2
Overall Diameter (inch)	73.2
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.5
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/10/2024 06:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..