

## EARTHMAX SR LOADER - Scheda tecnica



### Description

EARTHMAX SR LOADER è un pneumatico OTR particolarmente progettato per le operazioni di carico e spianamento, nonché per applicazioni di trasporto con dumper articolati. La sua carcassa All Steel rinforzata con cinture in acciaio multistrato e l'esclusiva miscela del battistrada offrono eccezionale resistenza a strappi e forature che si traducono in una vita prolungata dello pneumatico. EARTHMAX SR LOADER è dotato di un esclusivo disegno del battistrada che assicura ottime proprietà autopulenti e trazione eccellente su svariati tipi di terreno.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
<b>20.5 R 25</b>	CUT RESISTANT COMPOUND	94064250	E3/L3	**/*	177 B/186 A2	17.00/2.0		20.9	58.1	25.6	172.6	TL	116
<b>23.5 R 25</b>	CUT RESISTANT COMPOUND	94060283	E3/L3	**/*	185 B/195 A2	19.50/2.5	--	24.1	63.2	27.8	187.8	TL	137
<b>26.5 R 25</b>	CUT RESISTANT COMPOUND	94064847	E3/L3	**/*	193 B/202 A2	22.00/3.0		26.8	68.3	30	203.9	TL	158
<b>29.5 R 25</b>	CUT RESISTANT COMPOUND	94065608	E3/L3	**/*	200 B/208 A2	25.00/3.5		30.2	73.2	32.2	218.5	TL	185

Printed on 24/04/2024 05:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..