

## EM 937 (E3) - Scheda tecnica



### Description

EM 937 (E-3) è stato particolarmente progettato per dumper rigidi nelle applicazioni di miniera a cielo aperto. Lo pneumatico offre eccellente durabilità insieme ad elevata resistenza a tagli e strappi. EM 937 (E-3) è particolarmente idoneo per operazioni di servizio pesante.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Dumper rigido

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
14.00 - 25	STANDARD	94015443	E3/L3	28	10.00/1.5		14.8	53.9	24.4	161.6	TT	33
14.00 - 25	STANDARD	94015450	E3/L3	28	10.00/1.5		14.8	53.9	24.4	161.6	TL	33

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/02/2025 12:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..