

FARM 2000 PLUS - Specifiche tecniche



Description

FARM 2000 PLUS è un pneumatico agricoltura che si distingue per il maggior numero di ramponi al fine di garantire migliori performance nelle operazioni nel campo. Il battistrada profondo assicura una lunga vita dello pneumatico e ottima trazione, mentre l'eccellente mescola del battistrada si traduce in un'ottima resistenza a tagli e lacerazioni. FARM 2000 PLUS mostra delle straordinarie qualità di auto-pulitura oltre che un disegno particolare degli angoli dei ramponi che lo rendono idoneo per applicazioni nei campi e di trasporto.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	16.9 - 28
LI/SS	143 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1435
Static Loaded Radius (mm)	657
Rolling Circumference (mm)	4311
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	2725

Printed on 26/04/2024 11:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..