

## FARM 2000 - Specifiche tecniche



### Description

Lo pneumatico FARM 2000 è idoneo per trattori nelle applicazioni per la lavorazione del suolo. È stato realizzato con una miscela speciale resistente a tagli e lacerazioni che assicura una durabilità migliore. Grazie alla carcassa robusta, FARM 2000 offre elevata capacità di carico nonché trazione e proprietà di autopulitura eccellenti.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	250/80 - 16
LI/SS DRIVE WHEEL	113 A8
LI/SS FREE ROLLING	125 A8

## Dimensions US Standard

Usa code	94033614
Section Width (inch)	9.4
Overall Diameter (inch)	32.3
Static Loaded Radius (inch)	14.5
Rolling Circumference (inch)	95.6
Rim Rec	W 8
Rim Alt	W 7 ; W 9 ; W 8 L
ECE	E11-106R-003518
TRA Code	R1

## Load capacity (lbs)

mph / psi	41
5 FR	5090
15 FR	4330
20 FR	4080
25 FR	3640
5 DW	3550
15 DW	3020
20 DW	2840
25 DW	2540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/04/2025 09:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..