

FARM HIGHWAY TOUGH - Specifiche tecniche



Description

FARM HIGHWAY TOUGH è uno pneumatico ad alta velocità progettato per applicazioni di trasporto e di lavorazione del terreno con rimorchi e attrezzi agricoli . Offre un'elevata capacità di carico anche a velocità elevate e assicura un lungo ciclo di vita operativa.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	10.00 - 15 FI
LI/SS	128 J

Dimensions International Standard

Ply Rating	8
Section Width (mm)	274
Overall Diameter (mm)	853
Rim Rec	8 LB
ECE	E11-54R-0017870

Load capacity (Kg)

km/h / bar	4.10
100	1800

Printed on 26/04/2024 19:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..