

## FARM HIGHWAY TOUGH - Specifiche tecniche



### Description

FARM HIGHWAY TOUGH è uno pneumatico ad alta velocità progettato per applicazioni di trasporto e di lavorazione del terreno con rimorchi e attrezzi agricoli . Offre un'elevata capacità di carico anche a velocità elevate e assicura un lungo ciclo di vita operativa.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 9.5L - 15 FI |

## Dimensions International Standard

|                            |      |
|----------------------------|------|
| Ply Rating                 | 8    |
| Section Width (mm)         | 245  |
| Overall Diameter (mm)      | 766  |
| Static Loaded Radius (mm)  | 343  |
| Rolling Circumference (mm) | 2183 |
| Rim Rec                    | 7.00 |
| Rim Alt                    | 8 LB |

## Load capacity (Kg)

| km/h / bar | 4.10 |
|------------|------|
| 100        | 1215 |

Printed on 26/04/2024 17:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..