

FARM SPECIAL - Specifiche tecniche



Description

FARM SPECIAL è uno pneumatico per trattori idoneo per la lavorazione del terreno. La carcassa robusta garantisce un elevato livello di resistenza alle forature e una vita operativa più lunga, mentre le spalle arrotondate evitano danni al suolo proteggendo le colture preziose. FARM SPECIAL si distingue per il suo unico disegno del battistrada con elementi mud breaker che spezzano il fango ottimizzando le proprietà di autopulitura. Inoltre, la doppia angolazione dei tasselli assicura ottima trazione con minore slittamento.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	12.4 - 32
LI/SS	124 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	320
Overall Diameter (mm)	1360
Static Loaded Radius (mm)	634
Rolling Circumference (mm)	4137
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-005538
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.30
30	1600

Printed on 20/04/2024 10:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..