

FL 252 - Specifiche tecniche



Description

FL 252 è uno pneumatico idoneo per applicazioni di raccolta del fieno con ranghinatori/voltafieno nonché operazioni logistiche con carrelli elevatori. Lo pneumatico garantisce un'eccellente durabilità, mentre lo specifico disegno del battistrada assicura massima stabilità durante le operazioni di sollevamento.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Ranghinatore
Industriale: Carrello elevatore

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 7.00 - 12 |

Dimensions International Standard

| | |
|------------------------------|--------|
| Ply Rating | 14 |
| Section Width (mm) | 192 |
| Overall Diameter (mm) | 683 |
| Rim Rec | 5.00 S |

Load capacity (Kg)

| | km/h / bar | 9.00 |
|--|--------------------|------|
| | 25 LOAD WHEEL | 2755 |
| | 25 STEER WHEEL | 2120 |
| | 10 OTHER VEHICLES | 2755 |
| | 25 OTHER VEHICLES | 2120 |
| | STATIC SIDE LOADER | 3200 |

Printed on 27/04/2024 07:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..