

## FL 252 - Specifiche tecniche



### Description

FL 252 è uno pneumatico idoneo per applicazioni di raccolta del fieno con ranghinatori/voltafieno nonché operazioni logistiche con carrelli elevatori. Lo pneumatico garantisce un'eccellente durabilità, mentre lo specifico disegno del battistrada assicura massima stabilità durante le operazioni di sollevamento.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Ranghinatore  
Industriale: Carrello elevatore

Version	STANDARD
Type	TT
Tyre Size	8.25 - 15

## Dimensions US Standard

Usa code	94006939
Ply Rating	14
Section Width (inch)	9.4
Overall Diameter (inch)	33.7
Rim Rec	6.50
Rim Alt	7.0

## Load capacity (lbs)

mph / psi	116
15 LOAD WHEEL	9315
15 STEER WHEEL	7165
5 OTHER VEHICLES	9315
15 OTHER VEHICLES	7165
STATIC SIDE LOADER	10825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 14:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..