

FLOTATION 558 - Specifiche tecniche



Description

FLOTATION 558 è uno pneumatico Flotation a tele incrociate idoneo per mietitrici e presse per balle di fieno, autocisterne e rimorchi sia su strada che fuori strada. È particolarmente raccomandato in tutti i casi in cui la trazione è essenziale per una buona lavorazione del terreno oltre all'elevata capacità di carico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	500/45 - 22.5
LI/SS DRIVE WHEEL	136 A8/132 B
LI/SS FREE ROLLING	148 A8/144 B

Dimensions US Standard

Usa code	94006267
Ply Rating	12
Section Width (inch)	19.7
Overall Diameter (inch)	41.1
Static Loaded Radius (inch)	18.5
Rolling Circumference (inch)	124.7
Rim Rec	AG 16.00
ECE	E4-106R-002307

Load capacity (lbs)

mph / psi	33	36	39
5 FR	8860	9290	9720
10 FR	7970	8370	8750
20 FR	7090	7430	7780
25 FR	6330	6640	6940
30 FR	5700	5970	6170
5 DW	6290	6600	6910
10 DW	5670	5940	6220
20 DW	5040	5280	5530
25 DW	4500	4720	4940
30 DW	4050	4240	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/10/2024 08:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..