FLOTATION 648 - Specifiche tecniche

Description

FLOTATION 648 è particolarmente idoneo per trasporti su campo e su strada nonché applicazioni di spargitori. Alcune misure sono idonee per mietitrici/presse per balle di fieno. Il particolare disegno del battistrada consente il trasporto di carichi molto pesanti a pressioni basse, garantendo di conseguenza una compattazione ridotta del suolo e proteggendo nel contempo le colture da danni.

UM

International Standard

Construction

BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Spargitore

Version	STANDARD
Type	TL
Tyre Size	800/45 - 26.5
LI/SS DRIVE WHEEL	158 A8/155 B
LI/SS FREE ROLLING	170 A8/167 B

Dimensions International Standard

Ply Rating	12
Section Width (mm)	800
Overall Diameter (mm)	1393
Static Loaded Radius (mm)	631
Rolling Circumference (mm)	4185
Rim Rec	AG 28.00
ECE	E11-106R-004557

Load capacity (Kg)

km/h / bar	1.50	1.60	1.70
10 FR	7805	8105	8400
20 FR	7025	7295	7560
30 FR	6245	6485	6720
40 FR	5575	5790	6000
50 FR	5020	5210	5450
10 DW	5530	5740	5950
20 DW	4975	5165	5355
30 DW	4425	4590	4760
40 DW	3950	4100	4250
50 DW	3555	3690	3875

Printed on 24/04/2024 22:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..