

FLOTATION RIB 774 - Specifiche tecniche



Description

FLOTATION RIB 774 è ideale per applicazioni con assi non motrici, le operazioni di raccolta fieno e con rimorchi. È stato progettato per offrire una manovrabilità eccezionale ottimizzando la tempistica delle operazioni e garantendo un'elevata capacità di carico nonché un ciclo di vita prolungato degli pneumatici.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Mietitrebbia • Mietitrebbia • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	600/55 - 22.5
LI/SS FREE ROLLING	169 A8/166 B

Dimensions US Standard

Usa code	94006632
Ply Rating	16
Section Width (inch)	23.6
Overall Diameter (inch)	48.4
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	146.3
Rim Rec	AG 20.00
ECE	E11-106R-005944

Load capacity (lbs)

mph / psi	32	35	38
5 FR	16240	17080	17900
10 FR	14620	15380	16110
20 FR	12980	13670	14320
25 FR	11600	12200	12790
30 FR	10440	10980	11680

Printed on 26/04/2024 18:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..