

## FLOTATION TR 675 - Specifiche tecniche



### Description

FLOTATION TR 675 è ideale per le operazioni di trasporto su campo e su strada. Lo pneumatico è idoneo per l'utilizzo con rimorchi e attrezzi agricoli. FLOTATION TR 675 è stato progettato per garantire straordinaria trazione, elevata capacità di carico e un ciclo di vita prolungato dello pneumatico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

|                    |               |
|--------------------|---------------|
| Version            | DUAL BEAD     |
| Type               | TL            |
| Tyre Size          | 500/60 - 22.5 |
| LI/SS DRIVE WHEEL  | 155 A8/151 B  |
| LI/SS FREE ROLLING | 168 A8/164 B  |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 20              |
| Section Width (mm)         | 515             |
| Overall Diameter (mm)      | 1181            |
| Static Loaded Radius (mm)  | 542             |
| Rolling Circumference (mm) | 3604            |
| Rim Rec                    | AG 16.00        |
| Rim Alt                    | 15.00 ; 17.00   |
| ECE                        | E11-106R-004395 |

## Load capacity (Kg)

| km/h / bar | 3.70 | 3.80 | 4.00 |
|------------|------|------|------|
| 10 FR      | 7425 | 7545 | 7840 |
| 20 FR      | 6685 | 6790 | 7055 |
| 30 FR      | 5940 | 6035 | 6270 |
| 40 FR      | 5305 | 5390 | 5600 |
| 50 FR      | 4775 | 4850 | 5000 |
| 10 DW      | 5255 | 5340 | 5425 |
| 20 DW      | 4730 | 4805 | 4885 |
| 30 DW      | 4205 | 4275 | 4340 |
| 40 DW      | 3755 | 3815 | 3875 |
| 50 DW      | 3380 | 3435 | 3450 |

Printed on 20/04/2024 17:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..