

FLOTATION TR 675 - Scheda tecnica



Description

FLOTATION TR 675 è ideale per le operazioni di trasporto su campo e su strada. Lo pneumatico è idoneo per l'utilizzo con rimorchi e attrezzi agricoli. FLOTATION TR 675 è stato progettato per garantire straordinaria trazione, elevata capacità di carico e un ciclo di vita prolungato dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/60 - 22.5	DUAL BEAD	94050147	155 A8/151 B	168 A8/164 B	20	AG 16.00	15.00 ; 17.00	20.3	46.5	21.3	141.9	TL	E11-106R-004395
500/60 - 22.5	STANDARD	94019786	145 A8/142 B	157 A8/154 B	12	AG 16.00	15.00 ; 17.00	20.3	46.5	21.3	141.9	TL	E4-106R-002314
500/60 - 22.5	STANDARD	94019793	151 A8/ 148 B	163 A8/159 B	16	AG 16.00	15.00 ; 17.00	20.3	46.5	21.3	141.9	TL	E11-106R-003605
550/45 - 22.5	STANDARD	94047031	154 A8/150 B	166 A8/162 B	20	AG 16.00		21.4	42.1	0	0	TL	E4-106R-002723
550/60 - 22.5	STANDARD	94019809	148 A8/144 B	160 A8/156 B	12	AG 16.00		21.7	49.6	21.5	143.3	TL	E11-106R-004396
550/60 - 22.5	STANDARD	94019816	154 A8/150 B	167 A8/163 B	16	AG 16.00		21.7	49.6	21.5	143.3	TL	E11-106R-004397

Printed on 23/04/2024 08:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..