

FLOTATION TR 678 - Specifiche tecniche



Description

FLOTATION TR 678 è stato particolarmente sviluppato per attrezzi agricoli e rimorchi sia su strada sia fuori strada. Consente il trasporto di carichi pesanti a basse pressioni, assicurando allo stesso tempo una ridotta compattazione del suolo. Questo pneumatico garantisce eccellente trazione e ottime proprietà di autopulitura.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

| | |
|--------------------|---------------|
| Version | DUAL BEAD |
| Type | TL |
| Tyre Size | 600/40 - 22.5 |
| LI/SS DRIVE WHEEL | 157 A8 |
| LI/SS FREE ROLLING | 169 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 20 |
| Section Width (mm) | 615 |
| Overall Diameter (mm) | 1085 |
| Static Loaded Radius (mm) | 483 |
| Rolling Circumference (mm) | 3264 |
| Rim Rec | AG 20.00 |
| ECE | E11-106R-006501 |

Load capacity (Kg)

| km/h / bar | 4.10 |
|------------|------|
| 40 | 5800 |

Printed on 25/04/2024 22:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..