

FORESTLAND - Specifiche tecniche



Description

FORESTLAND è il modello agro-forestale più recente e innovativo di BKT. Questo pneumatico convenzionale è stato progettato specificamente per le applicazioni più gravose nei contesti forestali ma può essere impiegato anche in operazioni agricole quali taglio e pacciamatura nonché nelle attività di paesaggismo. Particolarmente resistente anche nelle condizioni operative più difficili grazie alla carcassa in poliesteri, FORESTLAND vanta una miscela del battistrada resistente a tagli e lacerazioni ed un fianco robusto che assicurano lunga durata allo pneumatico. Mentre il design della spalla aperta favorisce una trazione eccellente sui terreni soffici, il particolare disegno del battistrada con i suoi tasselli rigidi e rinforzati garantisce una buona aderenza su qualsiasi terreno nonché elevate proprietà di autopulitura. Infine, grazie al tallone rinforzato, FORESTLAND garantisce un alto livello di stabilità anche nelle operazioni più gravose.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	140 A8 / 137 B

Dimensions International Standard

Ply Rating	14
Section Width (mm)	378
Overall Diameter (mm)	1365
SRI (mm)	650
Rim Rec	W 13
Rim Alt	W 12, W 11
TRA Code	LS2

Load capacity (Kg)

km/h / bar	3.00
40	2500
50	2300

Printed on 01/05/2024 18:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..