

## FS 216 - Specifiche tecniche



### Description

FS 216 mostra un disegno robusto dei ramponi con angolazione ottimizzata e più larga per potenziare le performance in tema di trazione per macchine forwarder (autocaricanti) e macchine a strascico skidder. Lo pneumatico offre eccellente resistenza a tagli e strappi anche nelle condizioni operative più critiche, assicurando in ogni momento la massima protezione contro possibili danni.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Macchina a strascico

Version	STEEL BELTED
Type	TT
Tyre Size	18.4 - 30

## Dimensions US Standard

Usa code	94028115
Ply Rating	10
Section Width (inch)	18.4
Overall Diameter (inch)	62.1
Static Loaded Radius (inch)	28.5
Rolling Circumference (inch)	186.5
Rim Rec	DW 16 A
ECE	E11-106R-003638
TRA Code	LS2

## Load capacity (lbs)

mph / psi	30	25
5	8420	-
20	-	6010

Printed on 30/11/2023 01:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..