

GIANT TRAX - Specifiche tecniche



Description

GIANT TRAX è stato sviluppato per pale skid steer che operano su superfici ruvide come quelle che si possono trovare nei parchi rottami e nelle applicazioni di riciclaggio e minerarie. Il battistrada extra profondo con blocchi più larghi e più robusti assicura ottima trazione, stabilità e resistenza alla perforazione. La speciale miscela del battistrada si traduce in una straordinaria resistenza a tagli e lacerazioni abbinata all'eccellente resistenza contro l'usura su ogni tipo di terreno.

UM

International Standard

Construction

✚ BIAS

Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	14
Section Width (mm)	315
Overall Diameter (mm)	840
Static Loaded Radius (mm)	398
Rolling Circumference (mm)	2521
Rim Rec	9.75
ECE	E11-106R-005562

Load capacity (Kg)

	km/h / bar	6.20
	10	3075
	15	2430
	25	2245

Printed on 25/04/2024 18:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..