

INDUSTRIAL RIB F3 - Specifiche tecniche



Description

INDUSTRIAL RIB F3 è un pneumatico agro-industriale con disegno a blocchi del battistrada progettato per il trasporto su campo e su strada nonché per le operazioni di lavorazione del terreno con attrezzi agricoli e rimorchi. Questo pneumatico si distingue per la sua miscela straordinariamente resistente alle stoppie che lo rende idoneo per le condizioni operative più critiche, assicurando un lungo ciclo di vita del prodotto.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	11L - 15 SL
LI/SS	117 A6

Dimensions US Standard

Usa code	94055500
Ply Rating	12
Section Width (inch)	11
Overall Diameter (inch)	32
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-005311
TRA Code	F3

Load capacity (lbs)

mph / psi	62
20	2840
25	2560

Printed on 20/04/2024 08:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..