

INDUSTRIAL RIB F3 - Specifiche tecniche



Description

INDUSTRIAL RIB F3 è un pneumatico agro-industriale con disegno a blocchi del battistrada progettato per il trasporto su campo e su strada nonché per le operazioni di lavorazione del terreno con attrezzi agricoli e rimorchi. Questo pneumatico si distingue per la sua miscela straordinariamente resistente alle stoppie che lo rende idoneo per le condizioni operative più critiche, assicurando un lungo ciclo di vita del prodotto.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

Version	SPECIAL
Type	TL
Tyre Size	11L - 16 SL
LI/SS	116 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	279
Overall Diameter (mm)	830
Rim Rec	W 8 L
Rim Alt	8 LB ; 10 LB ; W 10 L
ECE	E11-106R-004304
TRA Code	F3

Load capacity (Kg)

km/h / bar	3.60
30	1250
40	1120

Printed on 20/04/2024 11:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..