

IT 400 - Scheda tecnica



Description

IT 400 è uno pneumatico con disegno del battistrada a blocchi per il principale impiego su strada nelle applicazioni di trasporto per rimorchi a pianale abbassato. Lo pneumatico è idoneo per applicazioni ad alta velocità e garantisce significativi risparmi di carburante.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Rimorchio a pianale abbassato

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.00 - 15	STANDARD	94008230	137/133 J	14	7.5	7.0 ; 8.0	10.8	36.4	16.1	108.1	TT	E11-54R-0018587
10.00 - 15	STANDARD	94008254	141/136 J	16	7.5	7.0 ; 8.0	10.8	36.4	16.1	108.1	TT	E11-54R-0018588
10.00 - 15	STANDARD	94008261	143/138 J	18	7.5	7.0 ; 8.0	10.8	36.4	16.1	108.1	TT	E11-54R-0019537
7.50 - 15	STANDARD	94008278	125/121 J	16	6.0	5.50 F ; 6.50	8.3	31.3	14	93	TT	E11-54R-0019535
8.25 - 15	STANDARD	94031818	129/125 J	14	6.50	6.0 ; 7.0	9.4	33.3	14.8	98.9	TL	E11-54R-0018586
8.25 - 15	STANDARD	94029020	131/126 J	16	6.50	6.0 ; 7.0	9.4	33.3	14.8	98.9	TT	E11-54R-0019536
8.25 - 15	STANDARD	94008292	129/125 J	14	6.50	6.0 ; 7.0	9.4	33.3	14.8	98.9	TT	E11E11-54R-0018586

Printed on 17/04/2024 07:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..