

LG 307 - Specifiche tecniche



Description

LG 307 è uno pneumatico per tappeti erbosi e il giardinaggio, idoneo per tosaerba. Lo specifico disegno del battistrada, rende lo pneumatico delicato sul terreno prevenendo danni al terreno erboso, facilitando nel contempo la manipolazione e le manovre.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Tosaerba

Version	STANDARD
Type	TL
Tyre Size	20 X 10.00 - 8

Dimensions US Standard

Usa code	94012848
Ply Rating	6
Section Width (inch)	10
Overall Diameter (inch)	19.5
Static Loaded Radius (inch)	8.5
Rolling Circumference (inch)	56.5
Rim Rec	8.00 I - 55 ; I - 70 ; I - 90
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003462

Load capacity (lbs)

mph / psi	32
10	1475

Printed on 19/04/2024 22:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..