

## LG 307 - Specifiche tecniche



### Description

LG 307 è uno pneumatico per tappeti erbosi e il giardinaggio, idoneo per tosaerba. Lo specifico disegno del battistrada, rende lo pneumatico delicato sul terreno prevenendo danni al terreno erboso, facilitando nel contempo la manipolazione e le manovre.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Tosaerba

Version	STANDARD
Type	TL
Tyre Size	20 X 12.00 - 10

## Dimensions International Standard

Ply Rating	4
Section Width (mm)	285
Overall Diameter (mm)	500
Static Loaded Radius (mm)	221
Rolling Circumference (mm)	1435
Rim Rec	8.5 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003463

## Load capacity (Kg)

km/h / bar	1.40
15	600

Printed on 19/04/2024 20:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..