

LIFTMAX LM 63 - Specifiche tecniche



Description

LIFTMAX LM 63 è stato particolarmente sviluppato per le operazioni industriali e di logistica. Il disegno del battistrada a 3-costole offre una bassa resistenza al rotolamento, una buona tenuta sul bagnato e un'usura uniforme del battistrada, insieme a una migliore maneggevolezza. Questo pneumatico radiale All Steel con cinture in acciaio multistrato assicura minori vibrazioni abbinate a una maggiore stabilità e comfort.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Mietitrebbia

Industriale: Tow Tractor • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	7.00 R 12
LI/SS	136 A5

Dimensions US Standard

Usa code	94066209
Overall Width (inch)	7.7
Overall Diameter (inch)	26.6
Rim Rec	5.00S

Load capacity (lbs)

mph / psi	145
15	4940

Printed on 23/04/2024 19:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..