

## LOADER PLUS - Specifiche tecniche



### Description

LOADER PLUS (L-3) è uno pneumatico a struttura diagonale, particolarmente progettato per loader. La mescola del battistrada offre delle caratteristiche di resistenza ad ogni tipo di taglio ed è ideale per operazioni di carico o livellamento.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Dozer • Pala caricatrice

OTR: Dozer • Pala caricatrice

Version	STANDARD
Type	TT
Tyre Size	14.00 - 25

## Dimensions International Standard

<b>Ply Rating</b>	20
<b>Overall Width (mm)</b>	375
<b>Overall Diameter (mm)</b>	1368
<b>Static Loaded Radius (mm)</b>	630
<b>Rolling Circumference (mm)</b>	4050
<b>Rim Rec</b>	10.00/1.5
<b>TRA Code</b>	L3

## Load capacity (Kg)

km/h / bar	7.00
10	8500

Printed on 19/04/2024 22:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..