

## LT TR 182 - Specifiche tecniche



### Description

LT TR 182 è idoneo per operazioni di trasporto con autocarri leggeri. Questo pneumatico ad alta velocità trova principale impiego sulla strada e riduce nettamente il consumo di carburante. Lo pneumatico LT TR 182 è anche facile da montare.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Autocarro leggero

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

## Dimensions US Standard

Usa code	94027927
Ply Rating	14
Section Width (inch)	8.1
Overall Diameter (inch)	28
Rim Rec	6.00 MH

## Load capacity (lbs)

	mph / psi	115
	62 LS	3030
	62 LD	2665

Printed on 25/04/2024 22:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..