

LT TR 182 - Scheda tecnica



Description

LT TR 182 è idoneo per operazioni di trasporto con autocarri leggeri. Questo pneumatico ad alta velocità trova principale impiego sulla strada e riduce nettamente il consumo di carburante. Lo pneumatico LT TR 182 è anche facile da montare.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Autocarro leggero

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
8 - 14.5	STANDARD	94027910	12	6.00 MH		8.1	28	TL
8 - 14.5	STANDARD	94027927	14	6.00 MH		8.1	28	TL

Printed on 25/04/2024 22:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..