MAGLIFT ECO RIB - Specifiche tecniche

Description

MAGLIFT ECO RIB è stato particolarmente sviluppato per rimorchi con attrezzature di supporto al suolo. La struttura rinforzata elimina il rischio di slittamento, mentre il particolare bordo di protezione del cerchio protegge lo pneumatico contro danni. MAGLIFT ECO RIB offre un controllo eccellente della sterzatura, elevata stabilità, bassa vibrazione nonché l'auto-allineamento del rimorchio. Ulteriori vantaggi sono bassa resistenza al rotolamento e ottima resistenza al calore, assicurando un'efficienza migliorata

UM

US Standard

Construction

- SOLID

Machinery

Industriale: Carrello elevatore

Version	STANDARD
Type	
Tyre Size	4.00 - 8

Dimensions US Standard

Usa code	94062706
Section Width (inch)	4.9
Overall Diameter (inch)	16.1
Rim Rec	3.75 I - 8

Load capacity (lbs)

mph / psi	-
3 OTHER VEHICLES	2225
5 OTHER VEHICLES	2015
15 OTHER VEHICLES	1710

Printed on 03/05/2024 18:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..