

## MAGLIFT ECO - Specifiche tecniche



### Description

MAGLIFT ECO è stato particolarmente sviluppato per applicazioni con carrelli elevatori. Lo pneumatico si distingue per il suo disegno con ramponi larghi che garantisce massima stabilità e distribuzione ottimizzata dei carichi. La sua struttura rinforzata elimina il rischio di slittamento, mentre il particolare bordo di protezione del cerchio protegge lo pneumatico contro danni. MAGLIFT ECO mostra eccellente trazione nonché bassa resistenza al rotolamento e ottima resistenza al calore, assicurando un'eccellente efficienza.

### UM

US Standard

### Construction

◆ SOLID

### Machinery

Industriale: Carrello elevatore

Version	STANDARD
---------	----------

Type	
------	--

Tyre Size	4.00 - 8
-----------	----------

## Dimensions US Standard

Usa code	94065868
Section Width (inch)	3.9
Overall Diameter (inch)	15.9
Rim Rec	3.00 D - 8

## Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	2095
15 STEER WHEEL	1610

Printed on 18/04/2024 22:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..