

## MAGLIFT EXCAVATOR - Specifiche tecniche



### Description

MAGLIFT EXCAVATOR è stato particolarmente sviluppato per escavatori gommati nelle operazioni di scavo, carico e costruzione stradale. Lo pneumatico è stato realizzato con una speciale miscela del battistrada, che garantisce straordinaria resistenza ad ogni tipo di taglio e un ciclo di vita prolungato dello pneumatico. Il design aggressivo del battistrada offre un elevato livello di comfort di manovrabilità combinato con un'eccellente trazione laterale anche in condizioni di servizio gravose oltre alle ottime proprietà di autopulitura. La struttura rinforzata del tallone assicura la migliore aderenza ed elimina ogni rischio di slittamento durante le operazioni, mentre la speciale forma del tallone facilita le operazioni di montaggio sul cerchio. MAGLIFT EXCAVATOR è uno pneumatico senza forature e manutenzione sul quale gli operatori possono contare.

### UM

International Standard

### Construction

◆ SOLID

### Machinery

Industriale: Escavatore

Version	STANDARD
Type	
Tyre Size	10.00 - 20

## Dimensions International Standard

Overall Width (mm)	246
Overall Diameter (mm)	1010
Rim Rec	8.00 - 20

## Load capacity (Kg)

km/h / bar	-
Static	7550
10	5450
25	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 14:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..