MAGLIFT GROSS - Specifiche tecniche

Description

Il nuovo MAGLIFT GROSS è stato progettato appositamente per i trattori portuali e per la movimentazione dei semirimorchi nelle applicazioni industriali, soprattutto nei centri di distribuzione, negli hub logistici e nei depositi di container. Il suo ampio profilo del battistrada garantisce una grande stabilità laterale e una maggiore sicurezza e manovrabilità nelle operazioni di sollevamento, anche con carichi pesanti. MAGLIFT GROSS è stato sviluppato con una struttura rinforzata che elimina i rischi di slittamento, mentre la sua speciale forma del tallone semplifica le operazioni di montaggio sul cerchio.

UM

International Standard

Construction

- SOLID

Machinery

Industriale: Trattore industriale

Version	STANDARD
Type	
Tyre Size	355/50 - 20

Dimensions International Standard

Section Width (mm)	311
Overall Diameter (mm)	840
Rim Rec	10.00 - 20

Load capacity (Kg)

km/h / bar	-
25 LOAD WHEEL	8970
25 STEER WHEEL	6900

Printed on 29/04/2024 17:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..