MAGLIFT PREMIUM - Scheda tecnica

Description

MAGLIFT PREMIUM è uno pneumatico solido particolarmente sviluppato per operazioni pesanti con carrelli elevatori in applicazioni portuali, minerarie o cantieri di demolizione. Il battistrada extra profondo (25% in più rispetto alla versione standard) con il suo disegno aggressivo e robusto offre eccezionale trazione anteriore e laterale oltre ad un controllo eccellente della sterzatura. La speciale mescola del battistrada si traduce in straordinaria resistenza a tagli e lacerazioni e prolunga la vita dello pneumatico. Ulteriori vantaggi sono la bassa resistenza al rotolamento e una corsa regolare.

UM

US Standard

Construction

- SOLID

Machinery

Industriale: Carrello elevatore

SIZE	Version	USACode	RIM REC	RIM ALT	SW	OD	Type
6.00 - 9	LIP	94055609	4.00 E - 9		5.4	21.1	
6.00 - 9	LIP - NON MARKING	94055906	4.00 E - 9		5.4	21.1	
6.00 - 9	STANDARD	94054299	4.00 E - 9		5.4	21.1	
6.00 - 9	STANDARD - NON MARKING	94055890	4.00 E - 9		5.4	21.1	
6.50 - 10	LIP	94055319	5.00 F - 10		5.9	22.9	
6.50 - 10	STANDARD	94055302	5.00 F - 10		5.9	22.9	
7.00 - 12	LIP	94055623	5.00 S - 12		6.4	26.1	
7.00 - 12	STANDARD	94055616	5.00 S - 12		6.4	26.1	

Printed on 20/04/2024 18:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..