

## MAGLIFT - Specifiche tecniche



### Description

MAGLIFT è stato particolarmente progettato per tutte le operazioni con carrelli elevatori nei settori industriali e nella logistica. Questo pneumatico pieno si distingue per l'elevata capacità di carico nonché per l'eccezionale confort. MAGLIFT offre una straordinaria resistenza alla perforazione che si traduce in una lunga vita dello pneumatico. La struttura rinforzata riduce il rischio di slittamento, mentre la particolare forma del tallone facilita il montaggio sul cerchio.

### UM

International Standard

### Construction

◆ SOLID

### Machinery

Industriale: Carrello elevatore

Version

STANDARD - NON MARKING

Type

Tyre Size

6.00 - 9

## Dimensions International Standard

TKPH	1
Section Width (mm)	141
Overall Diameter (mm)	529
Rim Rec	4.00 E - 9

## Load capacity (Kg)

	km/h / bar	-
25 LOAD WHEEL		1885
25 STEER WHEEL		1450

Printed on 26/04/2024 05:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..