

## MH TR 182 - Specifiche tecniche



### Description

MH TR 182 è idoneo per veicoli che trasportano case mobili. Lo pneumatico ad alta velocità per l'impiego principale su strada offre significativi risparmi di carburante. MH TR 182 assicura lunga durabilità e prestazioni elevate durante l'intero ciclo di vita del prodotto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Casa mobile

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	207
Overall Diameter (mm)	710
Rim Rec	6.00 MH

## Load capacity (Kg)

km/h / bar	6.90
100	1285

Printed on 23/04/2024 12:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..