

MH TR 182 - Scheda tecnica



Description

MH TR 182 è idoneo per veicoli che trasportano case mobili. Lo pneumatico ad alta velocità per l'impiego principale su strada offre significativi risparmi di carburante. MH TR 182 assicura lunga durabilità e prestazioni elevate durante l'intero ciclo di vita del prodotto.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Casa mobile

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
8 - 14.5	STANDARD	14	6.00 MH		207	710	TL
8 - 14.5	STANDARD	8	6.00 MH		207	710	TL
8 - 14.5	STANDARD	10	6.00 MH		207	710	TL
8 - 14.5	STANDARD	12	6.00 MH		207	710	TL

Printed on 23/04/2024 08:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..