

MINE STAR - Specifiche tecniche



Description

MINE STAR è uno pneumatico a tele incrociate che rappresenta un'ottima scelta per le operazioni di servizio pesante nelle miniere. Lo pneumatico si distingue per l'alta resistenza a tagli/strappi e perforazioni, ottimizzando l'efficienza operativa.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Veicolo per miniere sotterranee

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 55 X 19.00 - 25 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94067879 |
| Ply Rating | 50 |
| Section Width (inch) | 18.9 |
| Overall Diameter (inch) | 55.1 |
| Static Loaded Radius (inch) | 24.9 |
| Rolling Circumference (inch) | 168.5 |
| Rim Rec | 14.00 |
| TRA Code | L5 |

Load capacity (lbs)

| mph / psi | 145 |
|-----------|-------|
| 3 | 38100 |
| 5 | 33800 |
| 10 | 31400 |
| 15 | 28700 |

Printed on 24/04/2024 21:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..