

## MINE STAR - Scheda tecnica



### Description

MINE STAR è un pneumatico a tele incrociate che rappresenta un'ottima scelta per le operazioni di servizio pesante nelle miniere. Lo pneumatico si distingue per l'alta resistenza a tagli/strappi e perforazioni, ottimizzando l'efficienza operativa.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Veicolo per miniere sotterranee

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
<b>32 X 14.50/15 - 15</b>	STANDARD		28	11.0	11.50 ; 11.00 BD ; 10.50	350	825	0	0	TT
<b>35 X 15 - 15</b>	STANDARD		32	11.0	11.50 ; 11.00 BD	372	885	0	0	TT
<b>35 X 15 - 15</b>	STANDARD		20	11.0	11.50 ; 11.00 BD	372	885	0	0	TT
<b>35 X 15 - 15</b>	STANDARD		32	11.0	11.50 ; 11.00 BD	372	885	0	0	TL
<b>38 X 16 - 15</b>	STANDARD		32	11.5		400	990	0	0	TT
<b>38 X 16 - 15</b>	STANDARD		32	11.5		400	990	0	0	TL
<b>8.25 - 15</b>	STANDARD		20	6.5	6.0 ; 7.0	244	848	0	0	TT
<b>55 X 19.00 - 25</b>	STANDARD	L5	50	14.00		480	1400	632	4280	TL
<b>55 X 19.00 - 34</b>	STANDARD	L5	50	16.00		460	1435			TL

Printed on 02/12/2023 02:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..